

Elfcam® - Gigabit Ethernet Fiber Media Converter PoE (SX Serie)

The PoE Gigabit Ethernet Fiber Media Converter provides power and data transmission via Cat cables. PoE ports supply power at the standard of IEEE802.3af/at. Auto-sensing function can supply power to PD device (IEEE802.3af/at standard). If the PoE device disconnected, it would stop supplying power. The PoE switch features simple and reliable design, automatic identification of PoE supply voltage and power, speed, full duplex and Auto Uplink cable type.

This cost-effective switch can apply to wireless access point (AP) and IP-based surveillance Network solutions.

>> Feature

- ◆ IEEE 802.3af/at power on PoE ports
- ◆ Supply power to wireless access points and surveillance cameras over Cat cable
- ◆ PoE ports support MDI/MDIX
- ◆ Support PoE power up to 15.4W(IEEE802.3af)/25.5W(IEEE802.3at) for PoE ports
- ◆ PoE Lines: End-Span(12+,36-), Mid-Span(25+,78-)
- ◆ Support IEEE 802.3x flow control for Full-duplex Mode and back-pressure for Half-duplex Mode
- ◆ LED indicators for monitoring power, link, activity and speed
- ◆ Network Media: 10Base-T: Pair 2 Category 3(cat 3) and above UTP/STP(≤150m);100Base-TX: Pair 2 Category 5(cat 5) and above UTP/STP(≤150m);1000BASE-TX: 6 Category and above UTP(≤150m)
- ◆ Forwarding Mode: Store-And-Forward
- ◆ MTBF: 100,000 hours

>> Application

- ◆ Wireless Access Point
- ◆ IP Camera
- ◆ IP Phone
- ◆ Computer Networks

>> Specification

◆ 2 port PoE 10/100/1000M series

PoE Port	2 POE 10/100/1000Mbps
Uplink	UTP 10/100/1000Mbps, Fiber 1000Mbps
Bandwidth	1Gbps
Address Database Size	4K
Power Supply	DC52V
Max.Power Per Port	15.4W(IEEE802.3af) default, 25.5W(IEEE802.3at) optional
Network Protocols	IEEE 802.3i 10BASET; IEEE 802.3u 100BASETX; IEEE 802.3x Flow Control; IEEE 802.1af/at DTE Power via MDI; IEEE 802.3af/at, IEEE 802.3ab 1000BASE-T
LED Display	Power, POE, Ethernet
Transmission Distance	100meter for UTP ports; 0~20km for Fiber ports
Fiber Specification	Fiber Port: SC(SC/UPC, SC/APC, but SC/UPC is recommended), Wavelength/Distance: Single Fiber 1310nm/1550nm(20km)